

REBLOC 80XAS_8

Standard element

H2

W4

Installation

Free standing



Containment level


Working width

Impact severity level

H2 (covers H1 and N1)

W4 (covers W5, W6, W7 and W8)

ASI B (H2)



The maximum safety effect of the free standing systems is reached by the patented, integrated coupling system and an optimal reinforcement. No additional anchoring or embedment is required. The continuous tension bar gives the system maximum stability and ensures a high containment performance in the event of vehicle impact. Their modular construction and the ability to combine individual elements offer a wide range of usage options.

Additionally, the REBLOC 80XAS_8 is available as anchored soil system with H2/W2 (10 pins) or H2/W3 (4 pins). The system is installed on compacted soil. No additional foundation is required.

 0115 983 2304

 sales@hardstaffbarriers.com | enquiries@hardstaffbarriers.com

 A Division of Hill & Smith Ltd, Hillside, Gotham Road, Kingston-on-Soar, Nottingham, NG11 0DF


REBLOC RB80XAS_8

H2

W4

Standard element


Technical data



all dimensions in mm

Containment level	H2
Working width	W4
Impact severity level	ASI B
CE certification	✓
Installation	free standing on asphalt/concrete
Terminal elements	required, REBLOC 80X_4T (2 x screwbolts Ø 20 mm)
Dimensions L x W x H in mm	8000 x 590 x 800 mm
Weight/element	4800 kg
Elements/truck (24 t)	5 elements
Minimum installation length	80 m
Curve radius	$r \geq 250$ m, smaller radii on request
Coupling/exposed steel parts	fully integrated, exposed parts hot-dip galvanized

System elements - combinable



Terminal element
REBLOC 80X_4T
(inclination 1:5)